

ARMY RESEARCH LABORATORY



# Development and Testing of an Interface for Real-Time Visualization of Resin Flow in Composites

by William Green, Dale Shires,  
and Shawn Walsh

ARL-TR-1784

September 1998

19981019 034

Approved for public release; distribution is unlimited.

Reproduced From  
Best Available Copy

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

# **Army Research Laboratory**

Aberdeen Proving Ground, MD 21005-5069

---

**ARL-TR-1784****September 1998**

---

## **Development and Testing of an Interface for Real-Time Visualization of Resin Flow in Composites**

**William Green, Dale Shires, Shawn Walsh**  
Weapons and Materials Research Directorate, ARL

---

**Approved for public release; distribution is unlimited.**

---

---

## **Abstract**

---

The manufacture of polymer composite materials has benefited greatly from the development of computer-based simulation tools and sensor-based instrumentation. The present research offers a unique and powerful interface for collecting, integrating, analyzing, and rendering critical data related to a dynamic composite manufacturing process. These operations are executed in real time over the internet, permitting unprecedented flexibility and speed in deploying and using the manufacturing "tools." These tools include, but are not limited to, resin flow sensors, a model-based resin-flow reconstruction procedure, and a user friendly display for remotely manipulating and monitoring composite process events. The interface developed herein is critical not only in improving the fundamental visualization of a process but also as a means of practically communicating process information between geographically distinct locations. Thus, manufacturing concerns with only modest computer infrastructure can remotely leverage these tools to improve the quality, performance, and cost of their products without the need for significant investment in high performance computing infrastructure.

# Contents

<b>Acknowledgments</b>	<b>v</b>
<b>List of Figures</b>	<b>vii</b>
<b>1 Introduction</b>	<b>1</b>
<b>2 Developing a Visualization Tool</b>	<b>2</b>
2.1 Data Acquisition . . . . .	2
2.2 Reconstructing the Flow Front . . . . .	4
2.3 Developing the Visualization Interface . . . . .	6
<b>3 Flow Visualization - Case Studies</b>	<b>8</b>
3.1 Flat Panels . . . . .	8
3.2 Gun Mount Shield . . . . .	10
<b>4 Future Directions</b>	<b>12</b>
<b>5 Conclusions</b>	<b>14</b>
<b>References</b>	<b>17</b>
<b>Distribution List</b>	<b>19</b>
<b>Report Documentation Page</b>	<b>31</b>

INTENTIONALLY LEFT BLANK.

## Acknowledgments

Building the system described in this report required both creativity and lots of hard work. It also demanded meticulous attention to detail. This difficult task was mitigated by the highly-skilled group of scientists working in the embedded sensors program. The authors wish to thank all of these team members. Particular gratitude is owed to William Ballata and Fred Goetz for providing the instrumentation and SMARTweave experimental suites and to Colin Freese for the dynamic mesh refinement technique.

INTENTIONALLY LEFT BLANK.



## List of Figures

1	A SMARTweave $7 \times 7$ Sensor Grid. . . . .	2
2	Early Visualization Interface. . . . .	3
3	“Coarse” 2D Finite Element Mesh With Moving Flow Front. . . . .	6
4	“Fine” Finite Element Mesh With Moving Flow Front. . . . .	7
5	“Blocky” Effects From Coloring by Node. . . . .	8
6	Experimental Flat Panel With $16 \times 16$ Sensor Grid. . . . .	8
7	Flat Panel Experiments and Visualization. . . . .	9
8	Video Image of Flat Panel Experiment. . . . .	10
9	Ballistic Shield. . . . .	11
10	Ballistic Shield Experiments and Visualization. . . . .	13
11	Photo of In-Process Ballistic Shield Manufacture. . . . .	14

INTENTIONALLY LEFT BLANK.

# 1 Introduction

Composite materials are increasingly being used in Army combat systems. They offer strength, are lightweight, and as such are faster to deploy. Composite parts provide excellent protection from projectiles due to their energy-dispersing characteristics. Thick composites, in which additional protective materials such as ceramic plates can be placed, provide even better protection. An interesting ability with composites is that "in-situ" sensors can be incorporated into a composite part during its manufacture. These types of sensors can be used to monitor manufacturing processes while having little or no effect on final mechanical and structural properties. Sensors can indicate or delineate different phases of a manufacturing process and determine when the process is complete. Sensors remaining in a composite part after manufacture can also be used for health monitoring of the part over its lifetime. There is also currently an emphasis on the creation of "intelligent" or "smart" composite structures. Sensors in smart structures would provide data to be applied for controlling the manufacturing process. The development of smart structures addresses the lack of consistency and uniformity in composite part manufacturing today.

Liquid composite molding (LCM) processes such as resin transfer molding (RTM) and structural reaction injection molding (SRIM) are high-potential manufacturing methods for fabricating high-strength, high-volume composite parts. In general, a fiber preform is placed inside a matched-die mold and a reactive liquid resin is injected into the mold cavity through a number of ports into porous areas of the preform. A number of vents are also put into the mold cavity to prevent excessive pressures and help guide the resin flow.

However, composite parts are still generally cured in autoclaves, ovens, or presses using empirically based "recipe" cures. The variability in batch-processed raw materials, degradation during shelf life and out time, and environmental factors such as temperature and humidity can rarely be accounted for with the use of recipe cures. As a result, recipe cures usually require a high degree of post fabrication inspection and frequently produce less than optimum parts. They also have the potential to yield very high levels of scrap, especially for complicated geometries. In order to offset this to some degree, recipe cures are conservatively designed to maximize polymerization. This results in an unnecessary increase in process cycle time, inefficient equipment utilization, shorter tool life, and inflated processing costs. Most previous attempts to solve the problems inherent in recipe cures have concentrated on reducing batch-to-batch variations in raw materials and preproduction "proof" processing to accommodate those variations. This approach has been only moderately successful and not optimally cost effective.

Certainly a more practical and elegant approach that would overcome these problems would be to create a monitoring and control methodology that would be capable of assessing and subsequently modifying the actual condition of the material in real time or near real time as it is being processed. This methodology must acquire data that are indicative of where the flowing resin is in relation to the ports and vents in the mold cavity. Optimally, the actual location of the flow front would be determinable from the data. Current studies of multiregional flow in LCM processes do not determine actual flow front location using

real time sensor data during the process [1, 2, 3]. Another valuable flow state variable to know is flow front velocity, since location, speed, and direction would fully describe flow in the immediate future. Both the acquisition of data and reconstruction of the flow must be completed in a short time relative to the speed of the flow front. However, assuming that data acquisition and reconstruction of the flow is fast enough, the flow must still be quickly and accurately visualized. Furthermore, the location of the flow front must be easily interpretable from the visualization without requiring any detailed knowledge of the acquisition, reconstruction, and visualization methodology. This requires a robust combination of data acquisition, data analysis, and data visualization techniques to produce a fast and easily understood tool. Furthermore, to perform process control, the visualization tool must quickly respond to analysis results to modify flow parameters, e.g., port injection pressure, activation/shut off of injectors, etc.

In this report we describe the development of a visualization tool used to monitor and display the resin flow during fabrication of organic matrix composite laminates. The tool uses dynamic sensor data generated during part manufacture and was developed around a flexible and powerful scientific visualization framework. The successful integration of network-based data acquisition, fast finite element based reconstruction (smoothing) and contouring algorithms, and scientific visualization tools are described. The results of using the tool to visualize flow during fabrication of laminates, including flat panels and more complex parts, are discussed.

## 2 Developing a Visualization Tool

### 2.1 Data Acquisition

The U.S. Army Research Laboratory has developed a system known as SMARTweave (Sensors Mounted As Roving Threads) [4, 5, 6]. This is a novel approach of creating sensors by weaving flexible conductive fiber tows through composite preforms. Generally, a set of parallel tows is placed between two preform layers. A second set of parallel tows is placed at about  $90^\circ$  to the first set between different layers of preform material. Sets of tows are placed between different preform layers to prevent them from coming in contact with each other. These tows are then multiplexed with low-voltage electrical current being applied to one set of tows and sensing by voltage measurement being performed on the other set of tows. Basically, a sensor grid is formed in which sensor locations are where tows overlap one another. For example, a  $7 \times 7$  grid would yield 49 sensor locations as shown in Figure 1.




Figure 1: A SMARTweave  $7 \times 7$  Sensor Grid.

This type of setup is easily applied to simple preform shapes, such as relatively thin, flat panels. However, any number of tows or sets of tows in any orientation relative to each other can be placed in a composite preform. This is limited by the size and geometry of the preform itself and not by the size or geometry of the sensor tows. This means sensor grids can be placed throughout a preform of any thickness. Therefore, sensor grids can be placed in any part of a preform, including curved sections and around corners from one plane of the part to another. This gives the SMARTweave system high flexibility and wide applicability.

The SMARTweave system has the potential to collect data from any position in a composite preform and thus determine the current location of the global flow front. Early developments in the SMARTweave system produced a simple yet effective monitoring system. The multiplexed data collected at the grid overlap points, or sensor locations, are interpreted by customized National Instruments LabVIEW software running on a personal computer (PC). Based on predetermined thresholds, voltages at the sensors were indicative of whether or not resin had filled the sensor. The user was presented a graphical, two-dimensional (2D) representation of the preform that was colored based on voltage readings from the sensors or whether or not voltage thresholds had been exceeded. However, this visualization tool was constrained in two ways. First, only 2D cases could be fully visualized, and second, the 2D representation was constructed using rectangles delimited by the grid tows. This always produced a flow front with 90° steps as shown in Figure 2. Of course, more tows could be




Figure 2: Early Visualization Interface.

added to decrease this effect, but a great advantage of the SMARTweave system is that flow can be determined where there are no sensors by analyzing sparse sensor data. Flow in these areas could not be accurately shown with the “blocky” output from the early, PC-based, visualization tool. Also, adding more tows becomes impractical at a certain point.

The SMARTweave system is designed to be inexpensive and is taken “on the road” to perform analysis and gather data quickly. In order to visualize three-dimensional (3D)

experiments, a method was developed to transfer the data from the monitoring computer to a Silicon Graphics Incorporated (SGI) workstation in near real time. The SGI computer system was chosen for several reasons. Most importantly, the SGI has graphics hardware and software that allows users to easily render and manipulate 3D objects. This is done using Open Inventor, which is an object-oriented 3D toolkit based on Open GL (Graphics Library)[7]. Open GL is the interface by which the graphics hardware is controlled. Secondly, the OSF/Motif (Open Software Foundation) programming toolkit, which is built on top of the X11 code used for the UNIX windows environment on the SGI, is used to implement user interface components, such as menus, scroll bars, message boxes, and buttons. Mechanisms exist that incorporate the Motif and X11 components with the Open Inventor components.

Remote acquisition of process or laboratory data in real time or near real time is a powerful application that Internet access provides [8]. Routines were written on the PC and on the SGI to allow communication between the two existing TCP/IP (Transmission Control Protocol/Internet Protocol) network channels. The LabVIEW software on the PC has routines specifically for TCP/IP network communication. These routines were used to allow the PC user to input the internet address of the SGI workstation and the port to which it should connect. The PC then collects data at user set intervals and sends bursts of data over the network to the SGI workstation. The SGI workstation could have been used as the data acquisition device. However, an effective and highly portable PC-based data monitoring system existed, allowing dedication of the SGI to data analysis and flow rendering. The PC was fitted with a network card. Code was written for the SGI that allows the user to specify a TCP/IP socket which will act as a listener. This is done in the SGI user interface for the SMARTweave monitoring system. Most workstations in the SGI family are network-ready. This system of data acquisition and transfer has two advantages. It does not require specialized connectors to interface the two computers, and it allows for distributed data collection and visualization.

## 2.2 Reconstructing the Flow Front

Any number of sensors can be created in the SMARTweave system. However, it is desirable to use as few sensors as possible to collect data without losing information necessary for correctly determining flow front location. Currently, the capability exists to visualize sensor activity in near real time. Sensor points are turned on when they are filled as resin flows through the preform. However, we also want to know where the flow front is between the sensor points. Off-line capability has been developed to quickly reconstruct the flow front based on sensor locations and sensor activation (on) times [9]. In the 2D case, the reconstruction (smoothing) algorithm uses a triangular, quadratic, and computationally efficient element possessing 9 degrees-of-freedom (DOF) to locate the flow front in time based on a finite element model. The response of this particular smoothing element (in finite element notation) is dictated by three separate components and can be summarized as

$$[K^e]\{u^e\} = ([K_\epsilon^e] + [K_\alpha^e] + [K_\beta^e])\{u^e\} = \{f^e\}, \quad (1)$$

where  $K_\epsilon$ ,  $K_\alpha$ , and  $K_\beta$  symbolically represent the contributions of least-square error, gradient control, and curvature constraint, respectively, and  $u^e$  represents the nodal DOF. The interpolation function  $U^e$  within an element is written

$$U^e = [N]\{u^e\}, \quad (2)$$

where  $[N]$  are the element shape functions. The function  $U^e$  is related to the piecewise representation of the smooth function  $U(x, y)$ , defined in region  $\Omega$ , contained in Euclidean 2D space, by

$$\begin{aligned} \Phi(U) = \sum_{e=1}^{N_e} \Phi^e(U) = \sum_{e=1}^{N_e} \left\{ \frac{1}{2N_d^e} \sum_{i=1}^{N_d^e} \omega_i [U^e(x_i, y_i) - u_i]^2 \right. \\ \left. + \frac{\alpha}{2} \int_{\Omega_e} \left[ \left( \frac{\partial U^e}{\partial x} - \theta_x^e \right)^2 + \left( \frac{\partial U^e}{\partial y} - \theta_y^e \right)^2 \right] d\Omega \right. \\ \left. + \frac{\beta}{2} \int_{\Omega_e} \left[ \left( \frac{\partial U^e}{\partial^2 x} \right)^2 + 2 \left( \frac{\partial U^e}{\partial x \partial y} \right)^2 + \left( \frac{\partial U^e}{\partial^2 y} \right)^2 \right] d\Omega \right\}, \end{aligned} \quad (3)$$

where  $N_e$  is the number of finite elements,  $N_d^e$  is the number of data points falling within an element's space,  $u_i = u(x_i, y_i)$  is an arbitrary representative data set, and  $U^e$ ,  $\theta_x^e$ , and  $\theta_y^e$  are functions restricted to an element's domain. The data weighting constant, derivative, or gradient constraint constant, and the curvature constraint constant are represented by  $\omega$ ,  $\alpha$ , and  $\beta$ , respectively. In this case, the data set  $u_i$  is time. An expression for  $K_\epsilon$ ,  $K_\alpha$ ,  $K_\beta$ , and  $f^e$  results from the minimization of functional equation (3) with respect to the nodal DOF,  $\frac{\partial \Phi}{\partial u} = 0$ , and combination with equation (2). Further description of the mathematical model is available [9].

The algorithm determines the time solution for every node in the finite element model given the times sensors are activated. Thus, sparse data from a small number of sensors are analyzed to get data over the entire finite element model, which gives the resin flow front at discrete time intervals. Some elements will have all their nodes in the filled (on) state, some will have all their nodes in the unfilled (off) state, and some will have only one or two nodes in the filled state. Any element that has only one or two nodes on is considered to be partially filled with resin. A linear first approximation contouring methodology was used to determine what areas of partially filled elements should be considered filled. Contouring is generally not necessary for a relatively fine finite element mesh. However, since contouring is only applied to partial (filled) elements, it is only applied along the flow front. Contouring a relatively small number of partial elements can take less time than smoothing a very fine mesh in order to avoid contouring, since solving for such a mesh can be computationally intensive.

Consider the meshes shown in Figure 3. Figure 3(a) is a 2D finite element mesh, or grid, with the flow front moving from left to right. Figure 3(b) is the same grid with four-element refinement applied to the partial elements along the flow front. Four-element refinement is the process of creating four new elements that collectively describe the same area in space as the partial element they temporarily replace such that the flow front is delineated, or




Figure 3: “Coarse” 2D Finite Element Mesh With Moving Flow Front.

contoured, in the area of the partial element. The flow front is contoured in the partial element because each temporary new element is either completely in the flow region or completely out of the flow region. Figure 3(c) shows four-element refinement applied to the flow front later in time. The 12 elements down the middle of the grid have been reset to their original size and their original position. These elements have gone from partial elements to filled elements, whereas the 12 elements to their right have gone from empty elements to partial elements. As the flow front moves through the grid, nodes and elements are added and removed from it as necessary to contour partial elements.

Figure 4 shows a “fine” finite element mesh. Figure 4(a) is a refined grid with the flow front moving from left to right. Figure 4(b) is the same grid with elements repositioned along the flow front, but no further refinement. Nine elements are dynamically replaced with 36 elements in Figures 3(b) and 3(c). An original finer mesh is used in Figures 4(a) and 4(b) with simple element repositioning by node relocation. In order to use as coarse a grid as possible and minimize processing time, Dynamic Mesh Refinement (DMR) as shown in Figures 3(b) and 3(c) was used for flow front contouring.

## 2.3 Developing the Visualization Interface

Visualization and modeling in various areas of industry and research (e.g., textile materials, satellite images, virtual environments, etc.) is becoming increasingly important [10, 11, 12]. Realistic and accurate representation of objects or images is often necessary to meet design or system requirements. Open Inventor is designed to create and display 3D objects. All of the information about an object, such as its size, position, color, etc. is stored in a data structure known as a scene database. This scene database is visually similar to a tree structure. When the scene database, or scene graph, is displayed or rendered, it is traversed






Figure 4: "Fine" Finite Element Mesh With Moving Flow Front.

top-down, left-to-right. For any object, the design is logical and can be easily understood by traversing the scene graph. Finite element mesh geometry of an object can be formatted into an Open Inventor scene graph. The flow visualization interface quickly reads and formats a NASTRAN (finite element) file into an Open Inventor scene graph, which renders the object described by the file. However, any data file specifying nodes and nodal connectivity can be used [13]. The NASTRAN file is generated from Parametric Technology Corporation Pro/ENGINEER computer-aided design (CAD) software. The same finite element mesh used for rendering the object is used for smoothing and contouring, and also for performing flow simulations. Thus, the mesh should not be made too fine or too coarse. If the mesh is too fine, it results in slow rendering and contouring, but very good simulations. If the mesh is too coarse, it results in bad simulations, but fast rendering and contouring.

The time to complete smoothing, contouring, and rendering tasks must be small relative to the speed of the flow front in order to accurately display the flow front when new sensor data are received. If the computation time required to complete these tasks is too large the displayed flow front will lag in time behind the actual flow front. The visualization interface allows the user to turn off smoothing and contouring in order to view the sensor state only. The interface can also apply only smoothing to sensor data. In this case, the time solution for each node in the mesh is compared to the current time and any node with time less than or equal to the current time is a filled node. The interface uses color shading around nodes to distinguish between filled and empty nodes. However, shading by node gives the flow front a step-like, unsharp edge. This method gave better results than the PC-based "blocky" display, but still did not clearly delineate the flow front. An example of this is shown in Figure 5.

As can be seen in the figure, active sensors are displayed in white and unactivated sensors




Figure 5: “Blocky” Effects From Coloring by Node.

are shown in black. Resin-filled areas are shown in dark gray and void areas are shown in a lighter gray. Notice that the flow front is “fuzzy.” There is no clear defining line for the resin front. These results provided the impetus to develop element shading with DMR for contouring, which gives the flow front a well-defined edge without step-like contours between nodes. This approach shows the entire flow. An approach was also developed to show only the flow front, in which nodes on the front are marked by spheres and connected using straight-line segments. Results from these methods are shown in the following section.

### 3 Flow Visualization - Case Studies

#### 3.1 Flat Panels





Figure 6: Experimental Flat Panel With  $16 \times 16$  Sensor Grid.

The SGI visualization interface was first applied to monitoring flow in flat panels fabricated using the Seemann Composite Resin Infusion Molding Process (SCRIMP) [14]. SCRIMP uses a resin distribution system so that preforms with very large surface areas can be impregnated by vacuum force alone. This resin distribution system usually consists of a high-permeable medium placed between the fiber preform and the mold surface. It can also be augmented with grooves cut in the core or the mold. Using SCRIMP allowed testing of the visualization interface quickly and easily without

requiring use of an autoclave. The process also allows the flow fronts to be visually tracked.


Figure 6 shows a flat panel with a  $16 \times 16$  sensor grid. Sensor locations are delineated by the dark spheres coincident with the panel.

The panel was impregnated with resin (simulated with colored corn syrup) from the center. The center is marked by the small diamond-shaped hole. Figure 7 shows several rendering abilities of the scientific visualization system. Figure 7(a) shows the sensor data when the panel was about half filled with resin. Sensors that are on are colored white, and sensors that are off are colored black. Figure 7(b) shows the same sensor state with both reconstruction and contouring applied. The flow has been shaded by element (shown in white), and the flow front is well defined by using DMR. Figure 7(c) is the same flow showing only the flow front where DMR has been used.



(a) Sensor activation only.

(b) Sensor activation, reconstruction, and contouring.



(c) Sensor activation and flow front.

Figure 7: Flat Panel Experiments and Visualization.

Figure 8 is a video image snapshot of flow in the panel correlated in time with Figures 7(b) and 7(c). The flow in Figures 7(b), 7(c), and 8 is in very good agreement. It is very easy to apply reconstruction (for flow front rendering) only, reconstruction and contouring, or neither to sensor data in the visualization interface. Making the choice simply involves choosing a menu item from a list. This gives the user maximum flexibility in choosing how to visualize the flow and the flow front.




Figure 8: Video Image of Flat Panel Experiment.

### 3.2 Gun Mount Shield

The interface was also used to monitor flow in a much more complex composite part, the XM194 Gun Mount Shield, hereafter referred to as the ballistic shield. Again, SCRIMP was used to fabricate a thinner version of the full thickness ballistic shield. The actual ballistic shield part, in this case after some ballistic damage tests, is shown in Figure 9.

Tows were placed from front to back and from side to side across the top of the shield to form sensor grids. A total of six planar sensor grids were created, including one in the top, one in the back, one in each side, and two in the front. The PC visualization tool could only display one sensor grid at a time out of six possible grids. The SGI visualization tool continuously displays the entire ballistic shield, treating the shield as a single object with a set of properties to be rendered. Second, the SGI tool allows the user to move or spin the shield in space in order to view it from any angle.

The shield was impregnated with resin from the center of the back at the top. Figure 10(a) shows the sensor state after flow has proceeded through the top and into the front,




Figure 9: Ballistic Shield.

sides, and back of the shield. Sensors that are on are colored white, and sensors that are off are still colored black. Figure 10(b) shows the reconstructed and contoured flow for the sensor state, in which flow is shaded by element using DMR. Last, Figure 11 is a video image snapshot of flow in the shield correlated in time with Figures 10(a) and 10(b). Again, the flow in Figures 10(b) and 11 is in good agreement. This includes flow through edges and corners from one area of the shield to another. This is critical as effects like race tracking can occur along edges. The presence of race tracking often results in dry spot formation and other defects in molded composite parts [15].


The SGI visualization interface successfully monitored resin flow in a simple panel and the significantly more complex ballistic shield. It produced accurate flow reconstruction results, which when shaded by element and contoured using dynamic mesh refinement resulted in well defined flow front boundaries.

## 4 Future Directions


Resin flow in the flat panel and the ballistic shield was visualized in quasi-3D, in which flow is constrained in surfaces with no thickness. However, the 2D reconstruction algorithm is a simplification of the more general 3D case, which can reconstruct the flow front in full 3D. Visualization is significantly more difficult in full 3D, as individual faces of 3D elements with thickness will be shaded to produce an expanding “hollow solid” or shell representing the flow front, rather than filling of entire 3D elements. Of course, visualization in full 3D is necessary to show the flow front everywhere and not just near the surfaces, in thick composites. In the full 3D case, a tetrahedral finite element mesh and the 3D reconstruction algorithm would be used. The 3D algorithm would construct dynamic tetrahedral elements, which would be interrogated to determine what face(s) should be shaded for display.

Using the visualization interface to control the manufacturing processes for composites fabrication will be investigated in the near future as an appropriate control decision mechanism is added. The reconstruction algorithm solves for the time solution of every mesh node given the current sensor grid state. In addition, the algorithm can solve for the velocity at every mesh node. Knowledge of where the flow is (time) and where it is going (velocity) can be combined and utilized by some form of intelligent control. Control may be based on statistical methods, heuristic algorithms, neural networks or other artificial intelligence algorithms, or some other method.

Current work in RTM flow simulations has addressed designing and developing easy-to-use graphical interfaces for interactively changing simulation variables (e.g., number/location of ports and vents, open/close ports and vents, etc.) during the simulation [16]. The U.S. Army Research Laboratory, along with the Mechanical Engineering Department at the University of Minnesota, has developed a pure finite element methodology for RTM flow simulations [17, 18, 19]. It is based on the transient mass balance equation for the resin mass in conjunction with an implicit filling technique that provides solutions for both the pressure field as well as the resin front progression. Compared to the explicit Finite Element-Control Volume (FE-CV) methodologies used in other approaches, the new methodology developed



(a) Sensor activation only.



(b) Sensor activation, reconstruction, and contouring.

Figure 10: Ballistic Shield Experiments and Visualization.




Figure 11: Photo of In-Process Ballistic Shield Manufacture.

is faster and is more physically accurate. By using the SGI computer system with custom-built interfaces from X11/Motif and Open Inventor, the simulation tool is quick and easy to interact with and provides robust 3D graphics rendering. The capability to graphically animate simulation results has also been developed. Currently, the flow front reconstruction methodology and the simulation methodology, including animation, exist as separate applications. Another area of future investigation is the combination of the two methodologies in the SGI visualization interface for monitoring and flow front reconstruction/contouring. An animated simulation could be shown side by side with contoured real-time data. The simulation would continue in time step with the acquisition and reconstruction of actual data, showing how, if at all, one differs from the other. Simulation results can also be incorporated with the dynamic contouring (DMR) routines to provide data in areas relatively far from the flow. This would allow a simulation to guide the flow reconstruction early in time when there is relatively little sensor data, but become less dominant as more sensor data is received until finally the simulation is dominated by the sensor data.

## 5 Conclusions

The U.S. Army Research Laboratory has developed an SGI-based graphical visualization tool for monitoring and displaying resin flow in near real time in composites fabrication. It receives data over the internet from a data acquisition PC via TCP/IP routines on the PC and a network listener on the SGI. The tool uses a fast 2D reconstruction algorithm to locate the flow front in time based on a finite element model. Second, the tool can apply a contouring algorithm with dynamic mesh refinement to the flow front. Writing the tool in Open Inventor resulted in an easy-to-use-and-understand 3D graphical interface in which an



object described by a finite element mesh and the flow in the object are completely rendered.

Two different experiments were done to test the speed and accuracy of the visualization tool. In the first, resin flow in a flat panel was monitored and displayed (rendered) by the tool. There was good agreement between the actual flow front as recorded by video camera, the reconstructed flow front, and the reconstructed and contoured flow. In the second, resin flow in a thin version of the XM194 Gun Mount Shield was monitored and rendered by the tool. Again, there was good agreement between the actual flow front as recorded by video camera, the reconstructed flow front, and the reconstructed and contoured flow, including through edges from one plane of the shield to another.

Future work includes visualization of the flow front in full-3D, in which individual faces of 3D elements with thickness will be shaded to produce an expanding "hollow solid" or shell representing the flow front, rather than filling of entire 3D elements. Developing a control methodology based on the location (time) and the direction (velocity) of the flow front will also be investigated. Last, combining existing simulation methodology with the visualization tool will be investigated.

INTENTIONALLY LEFT BLANK.

## References

- [1] Ni, J., Y. Zhao, L. J. Lee, and S. Nakamura. "Analysis of Two-Regional Flow in Liquid Composite Molding." *Polymer Composites*, 18(2):pages 254–269, 1997.
- [2] Yalvac, S., A. Cohen, and M. Pollard. "A Review on Modeling of Resin Transfer Molding Process - Part 1: Preform Characterization Techniques." In Guceri [20], pages 1183–1993.
- [3] Yalvac, S., A. Cohen, and M. Pollard. "A Review on Modeling of Resin Transfer Molding Process - Part 2: Mold Filling Simulation." In Guceri [20], pages 1183–1993.
- [4] Walsh, S. M. "In-situ Sensor Method and Device." U.S. Patent number 5,210,499. May 1993.
- [5] Walsh, S. and M. Charmchi. "Free-Surface Flow Observations in the Resin Transfer Molding (RTM) Process." In D. Zumbrennen, J. Seyed-Yagoobi, V. Prasad, M. Charmchi, A. Lavine, M. Moallemi, N. Hussain, and T. Moon, editors, *American Society of Mechanical Engineers*, volume 261, pages 147–156. New Orleans, Louisiana, 1993.
- [6] Walsh, S. "Artificial Intelligence: Its Application to Composite Processing." In J. Janicki, V. Bailey, and H. Schjelderup, editors, *The Society for the Advancement of Materials and Process Engineering*, pages 1280–1291. Covina, California, 1990.
- [7] Wernecke, J. *The Inventor Mentor*. Addison-Wesley Publishing Company, Reading, Massachusetts, 1994.
- [8] Howarth, D. "Performing Data Acquisition Over the Internet." *Sensors: The Journal of Applied Sensing Technology*, 15(1):pages 49–51, 1998.
- [9] Freese, C. and S. Walsh. "Fluid Flow Reconstruction Modeling With Application to Liquid Molding Processing.", 1998. Submitted to the International Journal of Numerical Methods.
- [10] Groller, E., R. Rau, and W. Straßer. "Modeling and Visualization of Knitwear." *IEEE Transactions on Visualization and Computer Graphics*, 1(4):pages 302–310, 1995.
- [11] Craig, A., C. Kesselman, and S. Schwab. "Near Real-Time Satellite Image Processing: Metacomputing in CC++." *IEEE Computer Graphics and Applications*, pages 79–84, 1996.
- [12] Cremer, J., J. Kearney, and H. Ko. "Simulation and Scenario Support for Virtual Environments." *Computers and Graphics*, 20(2):pages 199–206, 1996.
- [13] Shires, D. "An Efficient Method for Parsing Large Finite Element Data Files." Technical Report ARL-TR-974, U.S. Army Research Laboratory, Aberdeen Proving Ground, Maryland, 1996.

- [14] W. H. Seemann, I. "Plastic Transfer Molding Techniques for the Production of Fiber Reinforced Plastic Structures." U.S. Patent number 4,902,215, February 1990.
- [15] Wang, T., C. Wu, and L. Lee. *Polymer Composites*, 15:pages 134, 1994.
- [16] Youssef, M. and G. Springer. "Interactive Simulation of Resin Transfer Molding." *Journal of Composite Materials*, 31(10):pages 954–980, 1997.
- [17] Mohan, R., S. Bickerton, D. Shires, S. Advani, and K. Tamma. "Analysis and Characterization of Flow Channels During Manufacturing of Composites by Resin Transfer Molding." In *Proceedings of Annual Meeting of the Society of Plastics Engineers*. 1997.
- [18] Mohan, R., D. Shires, K. Tamma, and N. Ngo. "Flow Channels and Fiber Impregnation Studies for the Process Modeling/Analysis of Complex Engineering Structures Manufactured by Resin Transfer Molding." In *Proceedings of the International Mechanical Engineering Congress and Exposition*. ASME, 1996.
- [19] Mohan, R., N. Ngo, and K. Tamma. "On a Pure Finite Element Based Methodology for Resin Transfer Mold Filling Simulations." Technical Report ARL-TR-975, U.S. Army Research Laboratory, Aberdeen Proving Ground, Maryland, 1996.
- [20] Guceri, S. I., editor. *First International Conference on Transport Phenomena in Processing*, Lancaster, Pennsylvania, 1992. Technomic Publishing Company, Inc.

NO. OF  
COPIES ORGANIZATION

2 DEFENSE TECHNICAL  
INFORMATION CENTER  
DTIC DDA  
8725 JOHN J KINGMAN RD  
STE 0944  
FT BELVOIR VA 22060-6218

1 HQDA  
DAMO FDQ  
DENNIS SCHMIDT  
400 ARMY PENTAGON  
WASHINGTON DC 20310-0460

1 OSD  
OUSD(A&T)/ODDDR&E(R)  
R J TREW  
THE PENTAGON  
WASHINGTON DC 20301-7100

1 CECOM  
SP & TRRSTRL COMMCTN DIV  
AMSEL RD ST MC M  
H SOICHER  
FT MONMOUTH NJ 07703-5203

1 PRIN DPTY FOR TCHNLGY HQ  
US ARMY MATCOM  
AMCDCG T  
M FISETTE  
5001 EISENHOWER AVE  
ALEXANDRIA VA 22333-0001

1 DPTY CG FOR RDE HQ  
US ARMY MATCOM  
AMCRD  
MG BEAUCHAMP  
5001 EISENHOWER AVE  
ALEXANDRIA VA 22333-0001

1 INST FOR ADVNCD TCHNLGY  
THE UNIV OF TEXAS AT AUSTIN  
PO BOX 202797  
AUSTIN TX 78720-2797

1 GPS JOINT PROG OFC DIR  
COL J CLAY  
2435 VELA WAY STE 1613  
LOS ANGELES AFB CA 90245-5500

NO. OF  
COPIES ORGANIZATION

1 DARPA  
B KASPAR  
3701 N FAIRFAX DR  
ARLINGTON VA 22203-1714

1 NAVAL SURFACE WARFARE CTR  
CODE B07 J PENNELLA  
17320 DAHLGREN RD  
BLDG 1470 RM 1101  
DAHLGREN VA 22448-5100

1 US MILITARY ACADEMY  
MATH SCI CTR OF EXCELLENCE  
DEPT OF MATHEMATICAL SCI  
MDN A MAJ DON ENGEN  
THAYER HALL  
WEST POINT NY 10996-1786

1 DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL CS AL TA  
2800 POWDER MILL RD  
ADELPHI MD 20783-1145

3 DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL CI LL  
2800 POWDER MILL RD  
ADELPHI MD 20783-1145

ABERDEEN PROVING GROUND

4 DIR USARL  
AMSRL CI LP (305)

NO. OF  
COPIES ORGANIZATION

1 DIRECTOR  
USARL  
AMSRL CP CA D SNIDER  
2800 POWDER MILL RD  
ADELPHI MD 20783

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR FSE T GORA  
PICATINNY ARSENAL NJ  
07806-5000

3 COMMANDER  
US ARMY ARDEC  
AMSTA AR TD  
R PRICE  
V LINDNER  
C SPINELLI  
PICATINNY ARSENAL NJ  
07806-5000

5 US ARMY TACOM  
AMSTA JSK  
S GOODMAN  
J FLORENCE  
AMSTA TR D  
B RAJU  
L HINOJOSA  
D OSTBERG  
WARREN MI 48397-5000

5 PM SADARM  
SFAE GCSS SD  
COL B ELLIS  
M DEVINE  
W DEMASSI  
J PRITCHARD  
S HROWNAK  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
F MCLAUGHLIN  
PICATINNY ARSENAL NJ  
07806-5000

NO. OF  
COPIES ORGANIZATION

5 COMMANDER  
US ARMY ARDEC  
AMSTA AR CCH  
S MUSALLI  
P CHRISTIAN  
R CARR  
M LUCIANO  
T LOUCEIRO  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR E FENNELL  
PICATINNY ARSENAL NJ  
07805-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR CCH  
PICATINNY ARSENAL NJ  
07806-5000

2 COMMANDER  
US ARMY ARDEC  
AMSTA AR  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR CCH P  
J LUTZ  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR FSF T  
C LIVECCHIA  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR QAC T/C  
C PATEL  
PICATINNY ARSENAL NJ  
07806-5000

NO. OF  
COPIES ORGANIZATION

2 COMMANDER  
US ARMY ARDEC  
AMSTA AR M  
D DEMELLA  
F DIORIO  
PICATINNY ARSENAL NJ  
07806-5000

3 COMMANDER  
US ARMY ARDEC  
AMSTA AR FSA  
A WARNASH  
B MACHAK  
C CHIEFA  
PICATINNY ARSENAL NJ  
07806-5000

8 DIRECTOR  
BENET LABORATORIES  
AMSTA AR CCB  
J KEANE  
J BATTAGLIA  
J VASILAKIS  
G FFIAR  
V MONTVORI  
J WRZUCHALSKI  
R HASENBEIN  
AMSTA AR CCB R S SOPOK  
WATERVLIET NJ 12189

1 COMMANDER  
SMCWV QAE Q B VANINA  
BLDG 44 WATERVLIET ARSENAL  
WATERVLIET NY 12189-4050

1 COMMANDER  
SMCWV SPM T MCCLOSKEY  
BLDG 253 WATERVLIET ARSENAL  
WATERVLIET NY 12189-4050

1 COMMANDER  
SMCWV QA QS K INSCO  
WATERVLIET ARSENAL  
WATERVLIET NY 12189-4050

1 COMMANDER  
US ARMY ARDEC  
AMSMC PBM K  
PICATINNY ARSENAL NJ  
07806-5000

NO. OF  
COPIES ORGANIZATION

1 COMMANDER  
US ARMY BELVOIR RD&E CTR  
STRBE JBC  
FORT BELVOIR VA 22060-5606

2 COMMANDER  
US ARMY ARDEC  
AMSTA AR FSP G  
M SCHIKSNIS  
D CARLUCCI  
PICATINNY ARSENAL NJ  
07806-5000

1 US ARMY COLD REGIONS RSRCH  
& ENGRNG LAB  
P DUTTA  
72 LYME RD  
HANOVER NH 03755

1 DIRECTOR  
USARL  
AMSRL WT L D WOODBURY  
2800 POWDER MILL RD  
ADELPHI MD 20783-1145

3 COMMANDER  
US ARMY MISSILE CMD  
AMSMI RD W MCCORKLE  
AMSMI RD ST P DOYLE  
AMSMI RD ST CN T VANDIVER  
REDSTONE ARSENAL AL  
35898-5247

2 US ARMY RSRCH OFC  
A CROWSON  
J CHANDRA  
PO BOX 12211  
RESEARCH TRIANGLE PARK NC  
27709-2211

5 PROJECT MANAGER  
TMAS  
SFAE GSSC TMA  
COL PAWLICKI  
K KIMKER  
E KOPACZ  
R ROESER  
B DORCY  
PICATINNY ARSENAL NJ  
07806-5000

NO. OF  
COPIES ORGANIZATION

1 PROJECT MANAGER  
TMAS  
SFAE GSSC TMA SMD  
R KOWALSKI  
PICATINNY ARSENAL NJ  
07806-5000

2 PEO FIELD ARTILLERY SYS  
SFAE FAS PM  
H GOLDMAN  
T MCWILLIAMS  
PICATINNY ARSENAL NJ  
07806-5000

2 PROJECT MGR CRUSADER  
G DELCOCO  
J SHIELDS  
PICATINNY ARSENAL NJ  
07806-5000

2 NASA LANGLEY RSRCH CTR  
MS 266  
AMSRL VS  
W ELBER  
F BARTLETT JR  
HAMPTON VA 23681-0001

2 COMMANDER  
DARPA  
J KELLY  
B WILCOX  
3701 N FAIRFAX DR  
ARLINGTON VA 22203-1714

6 COMMANDER  
WRIGHT PATTERSON AIR FORCE BASE  
WL FIV A MAYER  
WL MLBM S DONALDSON  
T BENSON TOLLE  
C BROWNING  
J MCCOY  
F ABRAHAMS  
2941 P ST STE 1  
DAYTON OH 45433

1 NSW CTR  
DAHLGREN DIV  
CODE G06  
DAHLGREN VA 22448

NO. OF  
COPIES ORGANIZATION

1 NAVAL RSRCH LAB  
CODE 6383  
I WOLOCK  
WASHINGTON DC 20375-5000

1 OFC OF NAVAL RSRCH  
MECH DIV CODE 1132SM  
YAPA RAJAPAKSE  
ARLINGTON VA 22217

1 NSW CTR  
CRANE DIV  
M JOHNSON  
CODE 20H4  
LOUISVILLE KY 40214-5245

1 DAVID TAYLOR RSRCH CTR  
SHIP STRUCTURES &  
PROTECTION DEPT  
J CORRADO CODE 1702  
BETHESDA MD 20084

2 DAVID TAYLOR RSRCH CTR  
R ROCKWELL  
W PHYLLAIER  
BETHESDA MD 20054-5000

1 DEFENSE NUCLEAR AGENCY  
INNOVATIVE CONCEPTS DIV  
DR R ROHR  
6801 TELEGRAPH RD  
ALEXANDRIA VA 22310-3398

1 DR FRANK SHOUP  
EXPEDITIONARY WARFARE DIV N85  
2000 NAVY PENTAGON  
WASHINGTON DC 20350-2000

1 OFC OF NAVAL RSRCH  
D SIEGEL 351  
800 N QUINCY ST  
ARLINGTON VA 22217-5660

1 JOSEPH H FRANCIS  
NSW CTR  
CODE G30  
DAHLGREN VA 2248



NO. OF  
COPIES ORGANIZATION

2 NSW CTR  
CODE G32 DON WILSON  
CODE G32 R D COOPER  
DAHLGREN VA 22448

4 NSW CTR  
CODE G33  
JOHN FRAYSSE  
ELDRIDGE ROWE  
TOM DURAN  
LAURA DE SIMONE  
DAHLGREN VA 22448

1 COMMANDER  
NAVAL SEA SYS CMD  
D LIESE  
2531 JEFFERSON DAVIS HWY  
ARLINGTON VA 22242-5160

1 NSW  
MARY E LACY CODE B02  
17320 DAHLGREN RD  
DAHLGREN VA 22448

1 NSW  
TECH LIB CODE 323  
17320 DAHLGREN RD  
DAHLGREN VA 22448

4 DIRECTOR  
LAWRENCE LIVERMORE NATL LAB  
R CHRISTENSEN  
S DETERESA  
F MAGNESS  
M FINGER  
PO BOX 808  
LIVERMORE CA 94550

1 LOS ALAMOS NATL LAB  
F ADDESSIO  
MS B216  
PO BOX 1633  
LOS ALAMOS NM 87545

1 LOS ALAMOS NATL LAB  
R M DAVIS  
PO BOX 2008  
OAK RIDGE TN 27831-6195

NO. OF  
COPIES ORGANIZATION

1 PENN STATE UNIV  
C BAKIS  
227 N HAMMOND  
UNIVERSITY PARK PA 16802

3 UDLP  
4800 EAST RIVER RD  
P JANKE MS170  
T GIOVANETTI MS236  
B VAN WYK MS389  
MINNEAPOLIS MN 55421-1498

4 DIRECTOR  
SANDIA NATL LAB APPLIED  
MECHANICS DEPT DIV 8241  
W KAWAHARA  
K PERANO  
D DAWSON  
P NIELAN  
PO BOX 969  
LIVERMORE CA 94550-0096

1 BATTELLE  
C R HARGREAVES  
505 KING AVE  
COLUMBUS OH 43201-2681

1 PACIFIC NORTHWEST LAB  
M SMITH  
PO BOX 999  
RICHLAND WA 99352

1 LAWRENCE LIVERMORE NATL LAB  
M MURPHY  
PO BOX 808 L282  
LIVERMORE CA 94550

1 DREXEL UNIV  
ALBERT S D WANG  
32ND & CHESTNUT ST  
PHILADELPHIA PA 19104

1 NC STATE UNIV  
CIVIL ENGRNG DEPT  
W RASDORF  
PO BOX 7908  
RALEIGH NC 27696-7908

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	PENN STATE UNIV RICHARD MCNITT 227 HAMMOND BLDG UNIVERSITY PARK PA 16802
1	PENN STATE UNIV RENATA ENGEL 245 HAMMOND BLDG UNIVERSITY PARK PA 16801
1	PURDUE UNIV SCHOOL OF AERO & ASTRO CT SUN W LAFAYETTE IN 47907-1282
1	STANFORD UNIV DEPT OF AERONAUTICS & AEROBALLISTICS DURANT BLDG S TSAI STANFORD CA 94305
1	UCLA MANE DEPT ENGR IV H THOMAS HAHN LOS ANGELES CA 90024-1597
2	UNIV OF DAYTON RSRCH INST RAN Y KIM AJIT K ROY 300 COLLEGE PARK AVE DAYTON OH 45469-0168
1	UNIVERSITY OF DAYTON JAMES M WHITNEY COLLEGE PARK AVE DAYTON OH 45469-0240
2	UNIV OF DE CTR FOR COMPOSITE MATERIALS J GILLESPIE M SANTARE 201 SPENCER LAB NEWARK DE 18716

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	UNIV OF IL AT URBANA CHAMPAIGN NATL CTR FOR COMPOSITE MATERIALS RSRCH 216 TALBOT LAB J ECONOMY 104 S WRIGHT ST URBANA IL 61801
1	UNIV OF KY LYNN PENN 763 ANDERSON HALL LEXINGTON KY 40506-0046
1	UNIV OF UT DEPT OF MECH & INDUSTRIAL ENGR S SWANSON SALT LAKE CITY UT 84112
3	THE UNIV OF TX AT AUSTIN CTR FOR ELECTROMECHANICS J PRICE A WALLS J KITZMILLER 10100 BURNET RD AUSTIN TX 78758-4497
3	VPI AND STATE UNIV DEPT OF ESM M W HYER K REIFSNIDER R JONES BLACKSBURG VA 24061-0219
1	UNIV OF MD DR ANTHONY J VIZZINI DEPT OF AEROSPACE ENGRNG COLLEGE PARK MD 20742
1	AAI CORP DR T G STASTNY PO BOX 126 HUNT VALLEY MD 21030-0126
1	JOHN HEBERT PO BOX 1072 HUNT VALLEY MD 21030-0126

NO. OF  
COPIES ORGANIZATION

1 ARMTEC DEFENSE PRODUCTS  
STEVE DYER  
85 901 AVE 53  
PO BOX 848  
COACHELLA CA 92236

2 ADVANCED COMP MATERIALS CORP  
P HOOD  
J RHODES  
1525 S BUNCOMBE RD  
GREER SC 29651-9208

1 SAIC  
DAN DAKIN  
2200 POWELL ST STE 1090  
EMERYVILLE CA 94608

1 SAIC  
MILES PALMER  
2109 AIR PARK RD S E  
ALBUQUERQUE NM 87106

1 SAIC  
ROBERT ACEBAL  
1225 JOHNSON FERRY RD STE 100  
MARIETTA GA 30068

1 SAIC  
DR GEORGE CHRYSSOMALLIS  
3800 W 80TH STREET  
STE 1090  
BLOOMINGTON MN 55431

4 ALLIANT TECHSYSTEMS INC  
C CANDLAND  
R BECKER  
L LEE  
R LONG  
D KAMDAR  
G KASSUELKE  
600 2ND ST NE  
HOPKINS MN 55343-8367

1 AMOCO PERFORMANCE PRODUCTS INC  
M MICHNO JR  
4500 MCGINNIS FERRY RD  
ALPHARETTA GA 30202-3944

NO. OF  
COPIES ORGANIZATION

1 APPLIED COMPOSITES  
W GRISCH  
333 NORTH SIXTH ST  
ST CHARLES IL 60174

1 BRUNSWICK DEFENSE  
T HARRIS  
STE 410  
1745 JEFFERSON DAVIS HWY  
ARLINGTON VA 22202

1 PROJECTILE TECHNOLOGY INC  
515 GILES ST  
HAVRE DE GRACE MD 21078

1 CUSTOM ANALYTICAL ENGR SYS INC  
A ALEXANDER  
13000 TENSOR LANE NE  
FLINTSTONE MD 21530

1 NOESIS INC  
ALLEN BOUTZ  
1110 N GLEBE RD STE 250  
ARLINGTON VA 22201-4795

1 ARROW TECH ASSO  
1233 SHELBURNE RD STE D 8  
SOUTH BURLINGTON VT 05403-7700

1 NSWC  
R HUBBARD G33 C  
DAHLGREN DIV  
DAHLGREN VA 22448-5000

5 GEN CORP AEROJET  
D PILLASCH  
T COULTER  
C FLYNN  
D RUBAREZUL  
M GREINER  
1100 WEST HOLLYVALE ST  
AZUSA CA 91702-0296

NO. OF COPIES	ORGANIZATION
7	CIVIL ENGR RSRCH FOUNDATION H BERNSTEIN PRESIDENT C MAGNELL K ALMOND R BELLE M WILLETT E DELO B MATTES 1015 15TH ST NW STE 600 WASHINGTON DC 20005
1	NIST STRCTRE & MCHNCS GROUP POLYMER DIV POLYMERS RM A209 GREGORY MCKENNA GAITHERSBURG MD 20899
1	DUPONT COMPANY COMPOSITES ARAMID FIBERS S BORLESKE DVLPMNT MGR CHESNUT RUN PLAZA PO BOX 80702 WILMINGTON DE 19880-0702
1	GENERAL DYNAMICS LAND SYSTEMS DIVISION D BARTLE PO BOX 1901 WARREN MI 48090
3	HERCULES INC R BOE F POLICELLI J POESCH PO BOX 98 MAGNA UT 84044
3	HERCULES INC G KUEBELER J VERMEYCHUK B MANDERVILLE JR HERCULES PLZ WILMINGTON DE 19894
1	HEXCEL M SHELENDICH 11555 DUBLIN BLVD PO BOX 2312 DUBLIN CA 94568-0705

NO. OF COPIES	ORGANIZATION
1	IAP RESEARCH INC A CHALLITA 2763 CULVER AVE DAYTON OH 45429
5	INSTITUTE FOR ADVANCED TECH T KIEHNE H FAIR P SULLIVAN W REINECKE I MCNAB 4030 2 W BRAKER LN AUSTIN TX 78759
1	INTEGRATED COMPOSITE TECH H PERKINSON JR PO BOX 397 YORK NEW SALEM PA 17371-0397
1	INTERFEROMETRICS INC R LARRIVA VICE PRESIDENT 8150 LEESBURG PIKE VIENNA VA 22100
1	AEROSPACE RES & DEV (ASRDD) CORP D ELDER PO BOX 49472 COLORADO SPRINGS CO 80949-9472
1	PM ADVANCED CONCEPTS LORAL VOUGHT SYSTEMS J TAYLOR PO BOX 650003 MS WT 21 DALLAS TX 76265-0003
2	LORAL VOUGHT SYSTEMS G JACKSON K COOK 1701 W MARSHALL DR GRAND PRAIRIE TX 75051
1	BRIGS CO JOE BACKOFEN 2668 PETERBOROUGH ST HERDON VA 22071-2443

NO. OF  
COPIES ORGANIZATION

1 SOUTHWEST RSRCH INSTITUTE  
JACK RIEGEL  
ENGRG & MTRL SCIENCES DIV  
6220 CULEBRA RD  
PO DRAWER 28510  
SAN ANTONIO TX 78228-0510

1 ZERNOW TECHNICAL SERVICES  
LOUIS ZERNOW  
425 W BONITA AVE SUITE 208  
SAN DIMAS CA 91773

1 ROBERT EICHELBERGER  
CONSULTANT  
409 W CATHERINE ST  
BEL AIR MD 21014-3613

1 DYNA EAST CORPORATION  
PEI CHI CHOU  
3201 ARCH ST  
PHILADELPHIA PA 19104-2711

2 MARTIN MARIETTA CORP  
P DEWAR  
L SPONAR  
230 EAST GODDARD BLVD  
KING OF PRUSSIA PA 19406

2 OLIN CORPORATION  
FLINCHBAUGH DIV  
E STEINER  
B STEWART  
PO BOX 127  
RED LION PA 17356

1 OLIN CORPORATION  
L WHITMORE  
10101 9TH ST NORTH  
ST PETERBURG FL 33702

1 RENNSAELER PLYTCHNC INST  
R B PIPES  
PRESIDENT OFC  
PITTSBURGH BLDG  
TROY NY 12180-3590

1 SPARTA INC  
J GLATZ  
9455 TOWNE CTR DRIVE  
SAN DIEGO CA 92121-1964

NO. OF  
COPIES ORGANIZATION

2 UNITED DEFENSE LP  
P PARA  
G THOMAS  
1107 COLEMAN AVE BOX 367  
SAN JOSE CA 95103

1 MARINE CORPS SYSTEMS CMD  
PROGRAM MGR GROUND WPNS  
COL RICK OWEN  
2083 BARNETT AVE SUITE 315  
QUANTICO VA 22134-5000

1 OFFICE OF NAVAL RES  
J KELLY  
800 NORTH QUINCEY ST  
ARLINGTON VA 22217-5000

2 NSWC  
CARDEROCK DIV  
R CRANE CODE 2802  
C WILLIAMS CODE 6553  
3A LEGGETT CIR  
ANNAPOLIS MD 21402

5 SIKORSKY  
H BUTTS  
T CARSTENSAN  
B KAY  
S GARBO  
J ADELMANN  
6900 MAIN ST  
PO BOX 9729  
STRATFORD CT 06601-1381

1 D ADAMS  
U WYOMING  
PO BOX 3295  
LARAMIE WY 82071

1 MICHIGAN ST UNIVERSITY  
R AVERILL  
3515 EB MSM DEPT  
EAST LANSING MI 48824-1226

1 AMOCO POLYMERS  
J BANISAUUKAS  
4500 MCGINNIS FERRY RD  
ALPHARETTA GA 30005

NO. OF  
COPIES ORGANIZATION

1     HEXCEL  
T BITZER  
11711 DUBLIN BLVD  
DUBLIN CA 94568

1     BOEING  
R BOHLMANN  
PO BOX 516 MC 5021322  
ST LOUIS MO 63166-0516

1     NAVSEA OJRI  
G CAMPONESCHI  
2351 JEFFERSON DAVIS HWY  
ARLINGTON VA 22242-5160

1     LOCKHEED MARTIN  
R FIELDS  
1195 IRWIN CT  
WINTER SPRINGS FL 32708

1     USAF  
WL/MLS OL A HAKIM  
5225 BAILEY LOOP 243E  
MCCLELLAN AFB CA 55552

1     PRATT & WHITNEY  
D HAMBRICK  
400 MAIN ST MS 114 37  
EAST HARTFORD CT 06108

1     DOUGLAS PRODUCTS DIV  
BOEING  
L J HART-SMITH  
3855 LAKEWOOD BLVD  
D800-0019  
LONG BEACH CA 90846-0001

1     MIT  
P LAGACE  
77 MASS AVE  
CAMBRIDGE MA 01887

1     NASA LANGLEY  
J MASTERS  
MS 389  
HAMPTON VA 23662-5225

NO. OF  
COPIES ORGANIZATION

1     CYTEC  
M LIN  
1440 N KRAEMER BLVD  
ANAHEIM CA 92806

2     BOEING ROTORCRAFT  
P MINGURT  
P HANDEL  
800 B PUTNAM BLVD  
WALLINGFORD PA 19086

2     FAA TECH CENTER  
D OPLINGER AAR 431  
P SHYPRYKEVICH AAR 431  
ATLANTIC CITY INTL AIRPORT NJ  
08405

1     NASA LANGLEY RC  
CC POE MS 188E  
NEWPORT NEWS VA 23608

1     LOCKHEED MARTIN  
S REEVE  
8650 COBB DR  
D/73-62 MZ 0648  
MARIETTA GA 30063-0648

1     WL/MLBC  
E SHINN  
2941 PST STE 1  
WRIGHT PATTERSON AFB OH  
45433-7750

2     IIT RESEARCH CENTER  
D ROSE  
201 MILL ST  
ROME NY 13440-6916

1     MATERIALS SCIENCES CORP  
BW ROSEN  
500 OFFICE CENTER DR  
STE 250  
FT WASHINGTON PA 19034

1     DOW UT  
S TIDRICK  
15 STERLING DR  
WALLINGFORD CT 06492

NO. OF  
COPIES ORGANIZATION

3 TUSKEGEE UNIVERSITY  
MATERIALS RSRCH LAB  
SCHOOL OF ENGR & ARCH  
S JEELANI  
H MAHFUZ  
U VAIDYA  
TUSKEGEE AL 36088

4 NIST  
R PARNAS  
J DUNKERS  
M VANLANDINGHAM  
D HUNSTON  
POLYMERS DIVISION  
GAITHERSBURG MD 20899

2 NORTHROP GRUMMAN  
ENVIRONMENTAL PROGRAMS  
R OSTERMAN  
8900 E WASHINGTON BLVD  
PICO RIVERA CA 90660

1 OAK RIDGE NATL LAB  
A WERESZCZAK  
BLDG 4515 MS 6069  
PO BOX 2008  
OAKRIDGE TN 37831-6064

1 COMMANDER  
US ARMY ARDEC  
T SACHAR  
INDUSTRIAL ECOLOGY CTR  
BLDG 172  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
USA ATCOM  
AVIATION APPLIED TECH DIR  
J SCHUCK  
FORT EUSTIS VA 23604-1104

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR SRE D YEE  
PICATINNY ARSENAL NJ  
07806-5000

NO. OF  
COPIES ORGANIZATION

7 COMMANDER  
US ARMY ARDEC  
AMSTA AR CCH B  
B KONRAD  
E RIVERA  
G EUSTICE  
S PATEL  
G WAGNECZ  
R SAYER  
F CHANG  
BLDG 65  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR QAC T  
D RIGOGLIOSO  
BLDG 354 M829E3 IPT  
PICATINNY ARSENAL NJ  
07806-5000

ABERDEEN PROVING GROUND

75 DIR USARL  
AMSRL CI C NIETUBICZ 394  
AMSRL CI C W STUREK 1121  
AMSRL CI CB R KASTE 394  
AMSRL CI S A MARK 309  
AMSRL SL B  
AMSRL SL BA  
AMSRL SL BE D BELY 328  
AMSRL WM B  
A HORST 390A  
E SCHMIDT 390A  
AMSRL WM BE  
G KELLER 390  
C LEVERITT 390  
D KOOKER 390A  
AMSRL WM BC  
P PLOSTINS 390  
D LYON 390  
J NEWILL 390  
S WILKERSON 390  
AMSRL WM BD  
R FIFER 390  
B FORCH 390A  
R PESCE-RODRIGUEZ 390  
B RICE 390A

NO. OF  
COPIES ORGANIZATION

AMSRL WM	R COATES 309
D VIECHNICK 4600	W DE ROSSET 309
G HAGNAUER 4600	AMSRL WM TD
J MCCAULEY 4600	T CHOU 4600
AMSRL WM MA	D DIETRICH 309
R SHUFORD 4600	A DAS GUPTA 309
S MCKNIGHT 4600	AMSRL WM TE J POWELL 120
AMSRL WM MB	AMSRL WM BA
B BURNS 4600	F BRANDON 120
W DRYSDALE 4600	W D AMICO 120
J BENDER 4600	AMSRL WM BB J BORNSTEIN 120
T BLANAS 4600	AMSRL WM BC A ZIELINSKI 390
T BOGETTI 4600	AMSRL WM BF J LACETERA 120
R BOSSOLI 120	
L BURTON 4600	
J CONNORS 4600	
S CORNELISON 120	
P DEHMER 4600	
R BOOLEY 4600	
B FINK 4600	
G GAZONAS 4600	
S GHIORSE 4600	
D GRANVILLE 4600	
D HOPKINS 4600	
C HOPPEL 4600	
D HENRY 4600	
R KASTE 4600	
R KLINGER 4600	
M LEADORE 4600	
R LIEB 4600	
E RIGAS 4600	
D SPAGNUOLO 4600	
W SPURGEON 4600	
J TZENG 4600	
AMSRL WM MB ALC	
A ABRAHAMIAN	
M BERMAN	
A FRYDMAN	
T LI	
W MCINTOSH	
E SZYMANSKI	
AMSRL WM MC T HYNES 4600	
AMSRL WM MD W ROY 4600	
AMSRL WM ME R ADLER 4600	
AMSRL WM T W MORRISON 309	
AMSRL WM TA	
W GILLICH 393	
W BRUCHEY 393	
T HAVEL 393	
AMSRL WM TC	



REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE September 1998		3. REPORT TYPE AND DATES COVERED Final, September 1997-April 1998
4. TITLE AND SUBTITLE Development and Testing of an Interface for Real-Time Visualization of Resin Flow in Composites			5. FUNDING NUMBERS  78M841	
6. AUTHOR(S)  William Green, Dale Shires, and Shawn Walsh				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army Research Laboratory ATTN: AMSRL-WM-MD Aberdeen Proving Ground, MD 21005-5069			8. PERFORMING ORGANIZATION REPORT NUMBER  ARL-TR-1784	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT  Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) <p>The manufacture of polymer composite materials has benefited greatly from the development of computer-based simulation tools and sensor-based instrumentation. The present research offers a unique and powerful interface for collecting, integrating, analyzing, and rendering critical data related to a dynamic composite manufacturing process. These operations are executed in real time over the internet, permitting unprecedented flexibility and speed in deploying and using the manufacturing "tools." These tools include, but are not limited to, resin flow sensors, a model-based resin-flow reconstruction procedure, and a user friendly display for remotely manipulating and monitoring composite process events. The interface developed herein is critical not only in improving the fundamental visualization of a process but also as a means of practically communicating process information between geographically distinct locations. Thus, manufacturing concerns with only modest computer infrastructure can remotely leverage these tools to improve the quality, performance, and cost of their products without the need for significant investment in high performance computing infrastructure.</p>				
14. SUBJECT TERMS  scientific visualization, user interfaces, composite structures, composite manufacturing			15. NUMBER OF PAGES 35	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT  UL	

INTENTIONALLY LEFT BLANK.

## USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-TR-1784 (Green) Date of Report September 1998

2. Date Report Received \_\_\_\_\_

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

CURRENT  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
E-mail Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)  
(DO NOT STAPLE)

---

DEPARTMENT OF THE ARMY


OFFICIAL BUSINESS

**BUSINESS REPLY MAIL**

FIRST CLASS PERMIT NO 0001,APG,MD

POSTAGE WILL BE PAID BY ADDRESSEE

DIRECTOR  
US ARMY RESEARCH LABORATORY  
ATTN AMSRL WM MD  
ABERDEEN PROVING GROUND MD 21005-5066



NO POSTAGE  
NECESSARY  
IF MAILED  
IN THE  
UNITED STATES

